

Ex&Im Top Equipment Supply Company

INDUSTRIAL ZINC OXIDE 98.5 %

TECHNICAL DATA SHEET

Product : Zinc Oxide CAS No : 1314-13-2
Grade : White Seal EC No : 215-222-5
Molecular formula : ZnO Date : 11.10.22

Parameters	UOM	LIMITS	
Zinc Oxide	%	98.67	Min
Acid Insoluble	%	0.15	Max
on as Fe	ppm	55	Max
ead as Pb	ppm	666	Max
admium as Cd	ppm	16	Max
opper as Cu	ppm	31	Max
anganese as Mn	ppm	10	Max
senic as As	ppm	6	Max
ılphur as S	%%	0.05	Max
eat loss at 110 Deg. C	%	0.20	Max
ırface Area	m2/gm	4.50(Min)	6.0 (Max)
)	%	1.25	Max
idity as SO3	%	Nil	
kalinity	%	0.05	Max
5 Mesh US Sieve	%	0.10	Мах
ecific Gravity	5.50 (Min)		5.68 (Max)
rbonate and substances ins	soluble in acids	F	Passes the test
pearance		White Amorn	hous Powder



Suggested Application

Tyre, Tread Rubber, Ceramics, Paints, Fertilizer, Catalysts, Electroplating, Additives, PVC, etc.

Packing

25 kg Net Wt. HDPE/Paper bags with inside liner/1000 Kg Jumbo bag. Other Packing modes may be available on request

Note

These are general specifications. We can offer product as per requirement of the customer.

Storage

To be stored in dry and well ventilated area.

UNIT 33 , $1^{\rm ST}$ FLOOR , IRAN PASSAGE , PAKDAMAN SQ , SHEMIRAN "NOU, TEHRAN- IRAN

TELLFAX:+98(21)77092972 MOBILE:+989108083316

E-MAIL: INFO@EXMPORT-CO.COM